

ARCHITECTURAL GRATES + DRAINS

Code 100TiTDi

Grate Style Ti

Range Threshold

Steel Grade 316

dimensions.

Category Made-to-Length

Channel Material Stainless Steel

Grates longer than 1500mm supplied in sections. Tile Inserts longer than 1200mm supplied in sections. Channels over 3000mm supplied in sections with joiner. +/-2mm tolerance on



100TiTDi Threshold with Sub-Sill

The 100TiTDi is a Threshold Drain for door track with sub sill tray featuring our 100mm wide Tile Insert.

For sliding and Hinged doors.

Featuring a linear stainless steel grate with concealed channel section connecting sill and sub-sill for door tracks and thresholds.

Allows door sills to be drained while having internal and external floor surfaces with no step down.


Suitable for tiles up to 12mm thick.

Please be aware that depending on the installation environment, for a pool installation or close to a surf beach, you may need to have your stainless steel grates electropolished.

SPECIFICATIONS + DIMENSIONS

Channel Width Channel Depth Length(s) Outlet Size 110mm Adjustable As Required N/A

STORMTECH COLOUR FINISHES



Electroplate finishes subject to natural variation with time and local environment. Factors such as pools/surf beaches may require electropolishing. Contact us for suitability.

PRODUCT APPLICATIONS

Aged / Health Care Drainage Balcony Drainage Commercial Drainage Multi-Residential Drainage Threshold Drainage Suspended Slab Drainage

Copyright © Stormtech Pty Ltd. Patent 733361. Drawings not to scale, please use dimensions shown. Downloaded 20/07/2025 (please check for updates)





Visit **stormtech.com.au** for tools + inspiration.